

MA-245



PA amplifiers with excellent performance and a variety of inputs and outputs. Suitable for shops, PA systems and distributed audio.

POWER	360 W maximum, 240 W RMS
RESPONSE	80-16,000 Hz ± 3 dB
DISTORTION	Harmonic: $< 1\%$ at 1 kHz
INPUTS	4 balanced mics/lines, combo (XLR and 6.3 mm jack) 600 Ohm 2 mV and 47,000 Ohm 150 mV, switchable 1 aux, 2 x RCA, 47,000 Ohm 300 mV 1 amp in, RCA 10,000 Ohm 1 V 1 tel. input, screw terminal blocks 600 Ohm 100 mV
OUTPUTS	1 line out, 2 x RCA 47,000 Ohm 1 V 1 pre out, RCA 600 Ohm 1 V 1 monitor, screw terminal blocks 600 Ohm 775 mV and 1 W 8 Ohm (aux input)
CONTROLS	Tone: Bass: ± 10 dB Treble: ± 10 dB Volume: inputs 1 to 4, aux and general volume
PHANTOM	24 V in mics 1 to 4, selectable
PRIORITY	Tel. input and mic. 1 depending on signal level, selectable
IMPEDANCE	4 Ohm and 100, 70 and 25 V lines, screw terminal blocks
POWER SUPPLY	230/115 V AC, 600 W and 24 DC, 312 W
DIMENSIONS	420 x 89 x 300 mm depth. 2 U 19" rack
WEIGHT	11.4 kg
OPTIONAL	MA-2N: mounts for assembly in 19" rack

© 2020 Copyright by FONESTAR SISTEMAS, S.A.