

MA-65GU



PA amplifiers with excellent performance and a variety of inputs and outputs. Suitable for shops, PA systems and distributed audio. This model has a USB/SD/MP3 recorder/player incorporated.

POWER	90 W maximum, 60 W RMS
RESPONSE	80-16,000 Hz ± 3 dB
DISTORTION	Harmonic: < 1%
INPUTS	3 balanced mics./ lines, combo (XLR and 6.3 mm jack) 600 Ohm 2 mV and 47,000 Ohm 150 mV, switchable. 1 aux, 2 x RCA 47,000 Ohm 300 mV 1 amp in, RCA 10,000 Ohm 1 V 1 telephone input, screw terminals 600 Ohm 100 mV
OUTPUTS	1 line out, 2 x RCA 47,000 Ohm 1 V 1 pre out, RCA 600 Ohm 1 V 1 monitor, screw terminals 600 Ohm, 775 mV and 1 W 8 Ohm (aux input)
CONTROLS	Tone: Bass: ± 10 dB Treble: ± 10 dB Volume: Input 1-3, aux, general volume and USB/SD/MP3 player
PLAYER	USB/SD/MP3 recorder/player
PHANTOM	24 V in mics. 1 to 3, selectable
PRIORITY	Tel. input and micro 1 through signal level, selectable
IMPEDANCE	4 Ohm and lines 100, 70 y 25 V, screw terminals
POWER SUPPLY	230/115 V AC, 130 W and 24 V DC, 82 W
DIMENSIONS	420 x 89 x 300 mm depth. 2 U 19" rack
WEIGHT	7.4 kg
OPTIONAL	MA-2N: mounts for assembly on a 19" U rack.

© 2020 Copyright by FONESTAR SISTEMAS, S.A.