

WA-2154D



Compact Hi-Fi stereo amplifier, 2 x 15 W RMS, with one optical digital audio or SPDIF input and two aux lines. Headphone output. Suitable for amplifying the TV digital audio output or for listening through headphones. Highly reliable with high quality audio. Compact and robust construction. Highly efficient class D amplification circuit.

POWER	2 x 15 W RMS at 4 Ohm
PROTECTION	Short circuit and temperature
RESPONSE	20-20,000 Hz
DISTORTION	Harmonic: 0.06 % at 1 kHz
INPUTS	1 optical SPDIF, toslink 1 coaxial SPDIF, RCA 2 aux lines, 2 x RCA and 3.5 mm stereo jack
OUTPUTS	4-8 Ohm loudspeakers, Euroblock 1 aux line, 2 x RCA 1 headphones, 3.5 mm stereo jack
CONTROLS	Input signal selector Digital input signal selector: optical or coaxial General volume Headphone volume
INDICATORS	LED power indicator LED indicator for input 1 signal
POWER SUPPLY	12 V DC, 2 A with adapter included
DIMENSIONS	205 x 25 x 108 mm depth
WEIGHT	0.6 kg (with adapter included)

© 2020 Copyright by FONESTAR SISTEMAS, S.A.