

WA-4100



Wall amplifier 100 W RMS. Integrated microphone, line and USB/SD/MP3 player inputs. Box for flush mount or surface mount. Specially designed for PA in gymnasiums, classrooms, sports centres, etc.

POWER	150 W maximum, 100 W RMS
RESPONSE	Microphones: 80-15,000 Hz Aux: 45-18,000 Hz
DISTORTION	Harmonic: <1% at 1 kHz
INPUTS	2 balanced mic./line, combo (XLR and 6.3 mm jack), 600 Ohm 3 mV and 47,000 Ohm 100 mV, switchable 1 stereo aux, 3.5 mm jack, 47,000 Ohm 300 mV 1 stereo aux, 2 x RCA, 47,000 Ohm 300 mV
OUTPUTS	1 line out, 2 x RCA, 1 V
FUNCTIONS	USB/SD/MP3 player for memory of up to 16 GB LED indicators for the output signal level
CONTROLS	Tones Bass: ± 10 dB at 100 Hz Treble: ± 10 dB at 10,000 Hz Volume: inputs 1 and 2, aux 1 and 2 and USB/SD/MP3 player
PHANTOM	15 V
IMPEDANCE	4 to 16 Ohm, 2 parallel outputs, screw terminals and banana plugs
POWER SUPPLY	230/115 V AC, 180 W maximum
COLOUR	White (RAL 9002)
DIMENSIONS	Total: 237 x 239 x 102 mm depth Insert: 219 x 182 x 91 mm depth

WEIGHT

3.4 kg

© 2020 Copyright by FONESTAR SISTEMAS, S.A.