Product data sheet



ATS4599

16-256 Zone Integrated Security Panel Int In Big Box

Intruder Alarm System

The Advisor MASTER is a full-blown intruder alarm system with more than 79 different input types. A maximum of 256 zones (inputs) can be programmed to operate over 16 independent groups (areas). Zones may be assigned to a specific area (offices, stores, etc.) or common to all (reception, canteen, etc.). Each area may have its separate RAS. The ATS4599 offers a large housing for additional accessories.



ATS4599

16-256 Zone Integrated Security Panel Int In Big Box

Technical specifications

System	
Product type	Integrated Access Control
Panel type	Hybrid
No. of keypads / readers	16
Data Gathering Panels (DGP)	15
No. of alarm groups	138
Specified cable	WCAT52
	WCAT54
Inputs	
Max no. of inputs	256
Onboard inputs	16
ATS1202 support	2
Outputs	
No. of outputs	255
No. of onboard outputs	4
Area	
No. of areas	16
User/Cards	
Max. no. of users	50
Users with name	50
Max. no. of cards	64000
10-digit PIN codes	2000
Access control	
Standard doors on control panel	16
Door groups	128
Floor groups	64
Intelligent doors on	48
4-door DGPs	
Communication	
Onboard transmission type	PSTN
Transmission extension	GSM/GPRS/IP
Databus type	RS485
Event log	
Alarm event log	1000
Access event log	1000
Electrical	
Power supply type	230 VAC
Power supply value	230 V 50 Hz/23 VAC 56 VA
Physical	
Physical dimensions	315 × 445 × 85 mm
Net weight	11200 g
Housing	Large Metal

Environmental

Operating temperature	0 to +50°C
Relative humidity	95% (non-condensing)
Environmental Class	Class II, indoor
IP rating	30

Standards & regulation

Compliancy	CE	
------------	----	--

As a company of innovation, UTC Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit UTC Fire & Security online or contact your sales representative.

