

## NC805C/14

4.2m/14ft tail call (connects to a QT602 call point or QT636/637 interface unit)



## Overview

A long 4.2m tail call lead for use with C-TEC's Quantec and 800 Series Call Systems.

Allows usersto remotely generate Standard calls from armchairs, beds, etc.

Comprises a pear-shaped call push, 4.2m(14ft) trailing lead and a 6.35mm remote jack plug.

Easily connects to the 6.35mm remote socket on compatible Quantec and 800 Series call points.

Activating the pear push or removing the tail call lead from a call point's remote socket will generate a Standard call.

## **Technical Specifications**

Compatibility   C-TEC's Quantec and 800 Series Call Systems.     Quiescent current   0mA (none).     Alarm current   Determined by the type of control equipment and number / type of field devices connected to the system.     Indicators   Reassurance LED on host call point will illuminate steady when call push is activated and/or removed.     Controls   Red Call button (generates a Standard call on activation when connected to a compatible Quantec or 800 Series call point).     Connections   6.35mm (quarter inch) jack plug.     Onboard Sounder   No.     Product dimensions (mm)   26 W x 21 H x 74 D mm (pear push). Lead is 4.2m (14ft) long.     Construction & finish   Plastic.     IP Rating   IP40.     Weight   118g		
Alarm current   Determined by the type of control equipment and number / type of field devices connected to the system.     Indicators   Reassurance LED on host call point will illuminate steady when call push is activated and/or removed.     Controls   Red Call button (generates a Standard call on activation when connected to a compatible Quantec or 800 Series call point).     Connections   6.35mm (quarter inch) jack plug.     Onboard Sounder   No.     Product dimensions (mm)   26 W x 21 H x 74 D mm (pear push). Lead is 4.2m (14ft) long.     Construction & finish   Plastic.     IP Rating   IP40.     Weight   118g	Compatibility	C-TEC's Quantec and 800 Series Call Systems.
Indicators   Reassurance LED on host call point will illuminate steady when call push is activated and/or removed.     Controls   Red Call button (generates a Standard call on activation when connected to a compatible Quantec or 800 Series call point).     Connections   6.35mm (quarter inch) jack plug.     Onboard Sounder   No.     Product dimensions (mm)   26 W x 21 H x 74 D mm (pear push). Lead is 4.2m (14ft) long.     Construction & finish   Plastic.     IP Rating   IP40.	Quiescent current	0mA (none).
Interest of a construction of the second o	Alarm current	
Connections6.35mm (quarter inch) jack plug.Onboard SounderNo.Onboard Infrared ReceiverNo.Product dimensions (mm)26 W x 21 H x 74 D mm (pear push). Lead is 4.2m (14ft) long.Construction & finishPlastic.IP RatingIP40.Weight118g	Indicators	
Onboard SounderNo.Onboard Infrared ReceiverNo.Product dimensions (mm)26 W x 21 H x 74 D mm (pear push). Lead is 4.2m (14ft) long.Construction & finishPlastic.IP RatingIP40.Weight118g	Controls	
No.Product dimensions (mm)26 W x 21 H x 74 D mm (pear push). Lead is 4.2m (14ft) long.Construction & finishPlastic.IP RatingIP40.Weight118g	Connections	6.35mm (quarter inch) jack plug.
Product dimensions (mm) 26 W x 21 H x 74 D mm (pear push). Lead is 4.2m (14ft) long.   Construction & finish Plastic.   IP Rating IP40.   Weight 118g	Onboard Sounder	No.
Construction & finish Plastic.   IP Rating IP40.   Weight 118g	Onboard Infrared Receiver	No.
IP Rating IP40. Weight 118g	Product dimensions (mm)	26 W x 21 H x 74 D mm (pear push). Lead is 4.2m (14ft) long.
Weight 118g	Construction & finish	Plastic.
	IP Rating	IP40.
Operating conditions/temperature	Weight	118g
	Operating conditions/temperature	-5°C to +40°C. Max. relative humidity 95% non-condensing.

Datasheet generated from https://www.electrika.com last updated Wednesday, January 16, 2019 11:45:58 AM