



QT432W

Quantec infrared/radio patient wrist pendant c/w wrist strap (push for call)



Overview

Allows patients in bedrooms and communal areas to remotely trigger standard calls via a Quantec infrared call point, ceiling receiver or radio receiver

Supplied on an adjustable wrist strap alleviating the need for long and potentially hazardous tail call leads.

10m line-of-sight IR transmitting range.

Radio coverage dependent on the Quantec receiving device used.

Powered by a user-replaceable 12V alkaline battery.

Can be programmed with a unique User ID so staff can see who is calling using a QT423 configurator.

Supplied with a sheet of coloured markable labels.

Technical Specifications

Compatibility	Compatible with C-TEC's Quantec call systems.
Type	Infrared/Radio.
Coverage	10m line-of-sight infrared coverage (940nm modulated @ 38 KHz); 60m typical radio coverage dependent on environmental factors (RF868.3 MHz).
Max battery size and type	12 Volt Type A23/23A (8LR50) alkaline (non-rechargeable). User replaceable.
Indicators	Confidence LED/battery status indicator.
Controls	1 x activation button (triggers a Standard call).
Product dimensions (mm)	47 W x 83 H x 16 D mm.
Construction & finish	TBC.
IP Rating	IP41.
Weight	30g.
Operating conditions/temperature	-5°C to +40°C. Max. relative humidity 95% non-condensing.
Notes	The transmitter's operation can be tailored to suit a specific site using a QT423 Configurator. Refer to the device's instructions for details.

Datasheet generated from <https://www.electrika.com> last updated Wednesday, January 16, 2019 11:46:06 AM