



MCB 1P 6kA C-10A 1M

MC110A

Architecture

Number of protected poles	1
Number of poles	1 P
Type of pole	1 P
Concurrently switching N-neutral	no
Curve	C

Main electrical features

Frequency	50/60 Hz
Rated short circuit breaking capacity I_{cn} AC according IEC60898-1	6 kA
Type of supply voltage	AC
Rated operational voltage U_e	230/400 V

Voltage

Rated insulation voltage	500 V
Rated impulse withstand voltage	4000 V

Electric current

Rated short circuit breaking capacity I_{cn} under 230V AC according IEC60898-1	6 kA
Rated service breaking capacity I_{cs} AC according IEC 60898-1	6 kA
Breaking capacity on 1 pole with 400 V NF 60947-2	3 kA
Rated ultimate short-circuit breaking capacity I_{cu} under 230V AC IEC 60947-2	6 kA
Magnetic regulating current at 40° C	5/10 I_n
min/maxi threshold value of the DC magnetic operation	7/15 I_n
min/maxi threshold value of the AC thermal operation	1,13/1,45 I_n
min/maxi threshold value of the DC thermal operation	1,13/1,45 I_n

Electric current / temperature

Rating current 20°C	10,8 A
Rating current 30°C	10 A
Rating current 35°C	9,6 A
Rating current 40°C	9,2 A
Rating current 45°C	8,8 A

Technical Properties

Rating current 50°C	8,4 A
Rating current 55°C	8 A
Rating current 60°C	7,6 A
Rating current 70°C	6,8 A

Current correction factors

Correction factor of magnetic tripping with 100 Hz	1,1
Correction factor of magnetic tripping with 200 Hz	1,2
Correction factor of magnetic tripping with 400 Hz	1,5
Correction factor of magnetic tripping with 60 Hz	1
Correction factor of rating current for 2 devices placed side-by-side	
Correction factor of rating current for 3 devices placed side-by-side	0,95
Correction factor of rating current for 4 and 5 devices placed side-by-side	0,9
Correction factor of rating current for 6 devices placed side-by-side	0,85

Power

Power loss per pole at In	1,63 W
Total power loss under IN	1,63 W

Endurance

Electric endurance in number of cycles	4000
Number of mechanical operations	20000

Dimensions

Depth of installed product	70 mm
Height of installed product	83 mm
Width of installed product	17,5 mm

Installation, mounting

Tightening torque	2,8Nm
-------------------	-------

Connection

type of connection	with screw
Top and bottom screw terminals connection capacity with flexible cable	1/16 mm ²
Top and bottom screw terminals connection capacity with rigid cable	1/25 mm ²

Equipment

Can be accessorized	no
---------------------	----

Standards

Standard text	EN 60898-1
European directive RoHs	voluntary compliance
European directive WEEE	concerned

Safety

Protection index IP	IP20
---------------------	------

Use conditions

Degree of pollution according to IEC 60664 / IEC 60947-2	2
Class of energy limitation I ² t	3
Altitude	2000 m
Storage temperature	-25 to 80 °C
Air humidity protection	for all climates
